

## Enhancements tab

### Overview



Advanced and third party integrations with the file gallery.

### Related Topics

- [SCORM](#)
- [PluginPlayScorm](#)

### To Access

From the [File Gallery](#) page, click the **Enhancements** tab.

Option	Description	Default
<a href="#">WebDAV access to Tiki</a>	Allow file gallery access with WebDAV  <i>use tiki-webdav.php as the URI of the WebDAV repository</i> 	Disabled
<a href="#">Use elFinder UI</a>	Alternative file manager with drag and drop capability	Enabled
<a href="#">Use elFinder on Toolbars</a>	Use elFinder in the popup on toolbar FileGallery buttons	Enabled
<a href="#">Enable elFinder debug mode</a>	Shows errors and warnings in the elFinder window and adds debugging information to service calls.	Disabled
<a href="#">Docs (WebODF)</a>	Docs enables viewing and editing Open Document Format files 	Disabled
<a href="#">Use PDF.js</a>	Uses PDF.js to display PDF files in web pages	Disabled
<a href="#">H5P support</a>	Handle H5P package files on upload. H5P enables the creation, sharing and reusing of interactive HTML5 content.	Disabled
Default Gallery	File gallery to create new H5P content in by default.	1
Whitelist	Allowed filetypes	json png jpg jpeg gif bmp t...
H5P Developer Mode	Use "patched" libraries?	Disabled
H5P Tracker User	Store H5P results	Disabled
Store user state	Allows users to resume at the point they last got to	Disabled
Save Frequency	How often to update user data.	60 seconds
Export	Allows users to export H5P content	Disabled
Hub Is Enabled	Updates libraries from h5p.org	Enabled
Site Key	H5P Site Key.  <i>Experimental</i>	None

Option	Description	Default
H5P UUID	H5P Unique ID. ⚠ <i>Experimental</i>	None
Content Type Updated	Last update. ⚠ <i>Experimental</i>	0 seconds
Check Requirements	Unused so far	Enabled
Send Usage Statistics	Unused so far ⚠ <i>Experimental</i>	Disabled
Request User Consent	Unused so far ⚠ <i>Experimental</i>	Disabled
LRS Content Types	Reporting (?) ⚠ <i>Experimental</i>	Disabled
Custom H5P Javascript Files	Comma-separated: library or "*" for all, path to the file and optional version number, one per line. 👉 <i>For example: H5P.Timeline,themes/js/h5p-custom-example.js,1.00</i>	None
Custom H5P CSS Files	Comma-separated library or "*" for all, path to the file and optional version number, one per line. 👉 <i>For example: H5P.Timeline,themes/css/h5p-custom-example.css,1.00</i>	None
<a href="#">Draw (SVG edit)</a>	Draw enables creating and editing SVG images in all wiki text areas	Disabled
<a href="#">Draw (SVG edit) hide buttons</a>	Hide buttons in Draw, HTML id, comma-separated. 👉 <i>Example: "tool_select, tool_fhpath, tools_line_show, tools_rect_show, tools_ellipse_show, tool_path, tools_shapelib_show, tool_text, tool_image, tool_zoom, tool_eyedropper"</i> 🔒	None
<a href="#">Separate base image</a>	Leaves the initially edited image as a separate file and stores the drawing separately 🔒	Disabled
<a href="#">Draw in user file gallery</a>	Users' drawings are stored in their user files gallery 🔒	Disabled
SCORM support	Handle SCORM package files on upload. SCORM is a standard used in learning management systems.	Disabled
SCORM Tracker	The ID number of the tracker used to store SCORM metadata	0
<a href="#">Vimeo upload</a>	Enables video upload to the Vimeo service. API keys are required and approval must be granted by Vimeo for the upload API.	Disabled

Option	Description	Default
Vimeo delete	Causes videos uploaded to the Vimeo service via Tiki file galleries to be deleted when the Tiki file is deleted. ⚠ <i>Permanently removes videos from the registered vimeo.com account.</i>	Disabled
Vimeo Default Gallery	The ID of the default file gallery in which to store the Vimeo reference	1
Vimeo consumer key	API consumer key	None
Vimeo consumer secret	API consumer secret	None
Vimeo access token	The access token that is automatically generated by Vimeo when API keys are requested.	None
Vimeo access token secret	The access token secret automatically generated by Vimeo when API keys are requested	None

The jQuery Sortable Tables feature must be activated for the sort feature to work.

Option	Description	Default
WebDAV access to Tiki	Allow file gallery access with WebDAV 👉 use <i>tiki-webdav.php</i> as the URI of the WebDAV repository 🗂	Disabled
Use elFinder UI	Alternative file manager with drag and drop capability	Disabled
Use elFinder on Toolbars	Use elFinder in the popup on toolbar FileGallery buttons	Enabled
Enable elFinder debug mode	Shows errors and warnings in the elFinder window and adds debugging information to service calls.	Disabled
Docs (WebODF)	Docs enables viewing and editing Open Document Format files 🗂	Disabled
Use PDF.js	Uses PDF.js to display PDF files in web pages	Disabled
H5P support	Handle H5P package files on upload. H5P enables the creation, sharing and reusing of interactive HTML5 content.	Disabled
Default Gallery	File gallery to create new H5P content in by default.	1
Whitelist	Allowed filetypes	json png jpg jpeg gif bmp t...
H5P Developer Mode	Use "patched" libraries?	Disabled

Option	Description	Default
H5P Tracker User	Store H5P results	Disabled
Store user state	Allows users to resume at the point they last got to	Disabled
Save Frequency	How often to update user data.	60 seconds
Export	Allows users to export H5P content	Disabled
Hub Is Enabled	Updates libraries from h5p.org	Enabled
Site Key	H5P Site Key. ⚠ <i>Experimental</i>	None
H5P UUID	H5P Unique ID. ⚠ <i>Experimental</i>	None
Content Type Updated	Last update. ⚠ <i>Experimental</i>	0 seconds
Check Requirements	Unused so far	Enabled
Send Usage Statistics	Unused so far ⚠ <i>Experimental</i>	Disabled
Request User Consent	Unused so far ⚠ <i>Experimental</i>	Disabled
LRS Content Types	Reporting (?) ⚠ <i>Experimental</i>	Disabled
Custom H5P Javascript Files	Comma-separated: library or "*" for all, path to the file and optional version number, one per line. 👉 <i>For example: H5P.Timeline,themes/js/h5p-custom-example.js,1.00</i>	None
Custom H5P CSS Files	Comma-separated library or "*" for all, path to the file and optional version number, one per line. 👉 <i>For example: H5P.Timeline,themes/css/h5p-custom-example.css,1.00</i>	None
<a href="#">Draw (SVG edit)</a>	Draw enables creating and editing SVG images in all wiki text areas	Disabled
<a href="#">Draw (SVG edit) hide buttons</a>	Hide buttons in Draw, HTML id, comma-separated. 👉 <i>Example: "tool_select, tool_fhpath, tools_line_show, tools_rect_show, tools_ellipse_show, tool_path, tools_shapelib_show, tool_text, tool_image, tool_zoom, tool_eyedropper"</i> 🔧	None
<a href="#">Separate base image</a>	Leaves the initially edited image as a separate file and stores the drawing separately 🔧	Disabled

Option	Description	Default
<a href="#">Draw in user file gallery</a>	Users' drawings are stored in their user files gallery 🗑️	Disabled
SCORM support	Handle SCORM package files on upload. SCORM is a standard used in learning management systems.	Disabled
SCORM Tracker	The ID number of the tracker used to store SCORM metadata	0
<a href="#">Vimeo upload</a>	Enables video upload to the Vimeo service. API keys are required and approval must be granted by Vimeo for the upload API.	Disabled
<a href="#">Vimeo delete</a>	Causes videos uploaded to the Vimeo service via Tiki file galleries to be deleted when the Tiki file is deleted. ⚠️ <i>Permanently removes videos from the registered vimeo.com account.</i>	Disabled
<a href="#">Vimeo Default Gallery</a>	The The ID of the default file gallery in which to store the Vimeo reference	1
Vimeo consumer key	API consumer key	None
Vimeo consumer secret	API consumer secret	None
<a href="#">Vimeo access token</a>	The access token that is automatically generated by Vimeo when API keys are requested.	None
<a href="#">Vimeo access token secret</a>	The access token secret automatically generated by Vimeo when API keys are requested	None

The jQuery Sortable Tables feature must be activated for the sort feature to work.

Option	Description	Default
<a href="#">WebDAV access to Tiki</a>	Allow file gallery access with WebDAV 👉 <i>use tiki-webdav.php as the URI of the WebDAV repository</i> 🗑️	Disabled
<a href="#">Use elFinder UI</a>	Alternative file manager with drag and drop capability	Disabled
<a href="#">Use elFinder on Toolbars</a>	Use elFinder in the popup on toolbar FileGallery buttons	Enabled
<a href="#">Enable elFinder debug mode</a>	Shows errors and warnings in the elFinder window and adds debugging information to service calls.	Disabled
<a href="#">Docs (WebODF)</a>	Docs enables viewing and editing Open Document Format files 🗑️	Disabled
<a href="#">Use PDF.js</a>	Uses PDF.js to display PDF files in web pages	Disabled

Option	Description	Default
H5P support	Handle H5P package files on upload. H5P enables the creation, sharing and reusing of interactive HTML5 content.	Disabled
Default Gallery	File gallery to create new H5P content in by default.	1
Whitelist	Allowed filetypes	json png jpg jpeg gif bmp t...
H5P Developer Mode	Use "patched" libraries?	Disabled
H5P Tracker User	Store H5P results	Disabled
Store user state	Allows users to resume at the point they last got to	Disabled
Save Frequency	How often to update user data.	60 seconds
Export	Allows users to export H5P content	Disabled
Hub Is Enabled	Updates libraries from h5p.org	Enabled
Site Key	H5P Site Key. ⚠ Experimental	None
H5P UUID	H5P Unique ID. ⚠ Experimental	None
Content Type Updated	Last update. ⚠ Experimental	0 seconds
Check Requirements	Unused so far	Enabled
Send Usage Statistics	Unused so far ⚠ Experimental	Disabled
Request User Consent	Unused so far ⚠ Experimental	Disabled
LRS Content Types	Reporting (?) ⚠ Experimental	Disabled
Custom H5P Javascript Files	Comma-separated: library or "*" for all, path to the file and optional version number, one per line. 👉 For example: H5P.Timeline,themes/js/h5p-custom-example.js,1.00	None
Custom H5P CSS Files	Comma-separated library or "*" for all, path to the file and optional version number, one per line. 👉 For example: H5P.Timeline,themes/css/h5p-custom-example.css,1.00	None

Option	Description	Default
<a href="#">Draw (SVG edit)</a>	Draw enables creating and editing SVG images in all wiki text areas	Disabled
<a href="#">Draw (SVG edit) hide buttons</a>	Hide buttons in Draw, HTML id, comma-separated. 👉 Example: "tool_select, tool_fhpath, tools_line_show, tools_rect_show, tools_ellipse_show, tool_path, tools_shapelib_show, tool_text, tool_image, tool_zoom, tool_eyedropper" 🔧	None
<a href="#">Separate base image</a>	Leaves the initially edited image as a separate file and stores the drawing separately 🔧	Disabled
<a href="#">Draw in user file gallery</a>	Users' drawings are stored in their user files gallery 🔧	Disabled
SCORM support	Handle SCORM package files on upload. SCORM is a standard used in learning management systems.	Disabled
SCORM Tracker	The ID number of the tracker used to store SCORM metadata	0
<a href="#">Vimeo upload</a>	Enables video upload to the Vimeo service. API keys are required and approval must be granted by Vimeo for the upload API.	Disabled
<a href="#">Vimeo delete</a>	Causes videos uploaded to the Vimeo service via Tiki file galleries to be deleted when the Tiki file is deleted. ⚠️ <i>Permanently removes videos from the registered vimeo.com account.</i>	Disabled
<a href="#">Vimeo Default Gallery</a>	The The ID of the default file gallery in which to store the Vimeo reference	1
Vimeo consumer key	API consumer key	None
Vimeo consumer secret	API consumer secret	None
<a href="#">Vimeo access token</a>	The access token that is automatically generated by Vimeo when API keys are requested.	None
<a href="#">Vimeo access token secret</a>	The access token secret automatically generated by Vimeo when API keys are requested	None

The jQuery Sortable Tables feature must be activated for the sort feature to work.

Option	Description	Default
<a href="#">WebDAV access to Tiki</a>	Allow file gallery access with WebDAV 👉 use <i>tiki-webdav.php</i> as the URI of the WebDAV repository 🔧	Disabled

Option	Description	Default
Use elFinder UI	Alternative file manager with drag and drop capability	Disabled
Use elFinder on Toolbars	Use elFinder in the popup on toolbar FileGallery buttons	Enabled
Enable elFinder debug mode	Shows errors and warnings in the elFinder window and adds debugging information to service calls.	Disabled
Docs (WebODF)	Docs enables viewing and editing Open Document Format files 🗑	Disabled
Use PDF.js	Uses PDF.js to display PDF files in web pages	Disabled
Use Viewer JS	Uses ViewerJS from <a href="http://viewerjs.org">http://viewerjs.org</a> if available (needs a separate install due to licensing restrictions), and allows displaying ODF files (odt, ods, odp) as well as pdf in web pages 🗑	Disabled
Viewer JS URI	Where ViewerJS is installed 🗑	files/viewerjs/ViewerJS/ind...
H5P support	Handle H5P package files on upload. H5P enables the creation, sharing and reusing of interactive HTML5 content.	Disabled
Default Gallery	File gallery to create new H5P content in by default.	1
Whitelist	Allowed filetypes	json png jpg jpeg gif bmp t...
H5P Developer Mode	Use "patched" libraries?	Disabled
H5P Tracker User	Store H5P results	Disabled
Store user state	Allows users to resume at the point they last got to	Disabled
Save Frequency	How often to update user data.	60 seconds
Export	Allows users to export H5P content	Disabled
Hub Is Enabled	Updates libraries from h5p.org	Disabled
Site Key	H5P Site Key. ⚠ Experimental	None
H5P UUID	H5P Unique ID. ⚠ Experimental	None



Option	Description	Default
Content Type Updated	Last update. <b>⚠ Experimental</b>	0 seconds
Check Requirements	Unused so far	Enabled
Send Usage Statistics	Unused so far <b>⚠ Experimental</b>	Disabled
Request User Consent	Unused so far <b>⚠ Experimental</b>	Disabled
LRS Content Types	Reporting (?) <b>⚠ Experimental</b>	Disabled
<a href="#">Draw (SVG edit)</a>	Draw enables creating and editing SVG images in all wiki text areas	Disabled
<a href="#">Draw (SVG edit) hide buttons</a>	Hide buttons in Draw, HTML id, comma-separated. <b>👉 Example:</b> "tool_select, tool_fhpath, tools_line_show, tools_rect_show, tools_ellipse_show, tool_path, tools_shapelib_show, tool_text, tool_image, tool_zoom, tool_eyedropper" <b>🔑</b>	None
<a href="#">Separate base image</a>	Leaves the initially edited image as a separate file and stores the drawing separately <b>🔑</b>	Disabled
<a href="#">Draw in user file gallery</a>	Users' drawings are stored in their user files gallery <b>🔑</b>	Disabled
SCORM support	Handle SCORM package files on upload. SCORM is a standard used in learning management systems.	Disabled
SCORM Tracker	The ID number of the tracker used to store SCORM metadata	0
<a href="#">Vimeo upload</a>	Enables video upload to the Vimeo service. API keys are required and approval must be granted by Vimeo for the upload API.	Disabled
<a href="#">Vimeo delete</a>	Causes videos uploaded to the Vimeo service via Tiki file galleries to be deleted when the Tiki file is deleted. <b>⚠ Permanently removes videos from the registered vimeo.com account.</b>	Disabled
<a href="#">Vimeo Default Gallery</a>	The The ID of the default file gallery in which to store the Vimeo reference	1

Option	Description	Default
Vimeo consumer key	API consumer key	None
Vimeo consumer secret	API consumer secret	None
<a href="#">Vimeo access token</a>	The access token that is automatically generated by Vimeo when API keys are requested.	None
<a href="#">Vimeo access token secret</a>	The access token secret automatically generated by Vimeo when API keys are requested	None

*The jQuery Sortable Tables feature must be activated for the sort feature to work.*

[SCORM tab](#)