

New in [Tiki23](#)

## Introduction

GlitchTip is an Open Source error tracking system and you can self-host GlitchTip or subscribe to [GlitchTip.com](#)

It also does:

- Uptime Monitoring
- Application Performance Monitoring (not yet supported in Tiki, but you can use [Real User Measurement](#)).

The recommended and fully functional way to track your Tiki errors in GlitchTip is (where [yourtiki.org](#) is your Tiki instance and [glitchtip.example.com](#) is your GlitchTip instance):

Setup GlitchTip for a new project:

- Add a new project in your GlitchTip instance by clicking the "Create New Project"
- Choose PHP as your platform, input the project name ([yourtiki.org](#)) and select your team

# Create a New Project

## Platform

The primary platform for this project. Used for documentation.

Filter platforms

Popular

Browser

Server

Mobile

Desktop

All

JavaScript

React

Django

Python

Flask

Rails

Express

Laravel

Symfony2

Java

C#

Elixir

PHP

Ruby

Node.js

React-Native

Angular

Project Name

yourtiki.org

Assign a team

test



Create Project

- Tiki23+ bundles sentry/sdk so you should not run Composer
- Note and copy your DSN from the left panel, it will be used in the Tiki .ini file:

# DSN

Most instructions will have a spot that says "your DSN here". Copy the DSN and paste it into that spot.

DSN

<https://4bd1dec539c9496b9d3f3f3ef5bd284f70@glitchtip.example.com/4>

Security Endpoint

<https://bugsbucket.evolutadata.com>

## 1.1.3. Create a new system configuration .ini file or add a new rule and modify local.php:

It is not recommended to use tiki-admin.php Setup Error Tracking feature in Admin > General > Error Tracking because it loads later and will miss some error messages

For more information about system configuration and tiki.ini (or tiki.ini.php), see: [System Configuration](#)

- Create a new folder named tikiconfig outside the web accessible directory, and inside this folder create a new prefs.ini file containing

```
../tikiconfig/prefs.ini
```

```
[glitchtip] preference.error_tracking_enabled_php = y preference.error_tracking_enabled_js = y
preference.error_tracking_dsn =
https://4bd1dec539c9496b9d3f3ef5bd284f70@glitchtip.example.com/4
```

Of course, replace the preference.error\_tracking\_dsn link with the DSN generated by GlitchTip

- Now add the following lines to your existing local.php file in the /db folder

```
db/local.php
```

```
if (is_readable('../tikiconfig/prefs.ini')) { $system_configuration_file = '../tikiconfig/prefs.ini'; } else {
trigger_error('Ini file not found: ../tikiconfig/prefs.ini', E_USER_WARNING); }
$system_configuration_identifier = 'glitchtip';
```

## 1.1.4. You are done

Check the errors reported in your GlitchTip instance, by navigating to your project.

Original commit: [https://gitlab.com/tikiwiki/tiki/-/merge\\_requests/825](https://gitlab.com/tikiwiki/tiki/-/merge_requests/825)

## Sample rate

Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)

Preference name: error\_tracking\_sample\_rate

## Usage for the Tiki development process

- [Using GlitchTip as part of the Tiki development process](#)

## Related links

- <https://glitchtip.com/blog/2023-2-17-analytics>