

Memcache tab

Overview

Use this tab to configure [performance](#) settings when using PHP memcache

Related Topics

- [Performance](#)
- [Cache](#)

To Access

From the [Performance Admin Panel](#) page, click the **Database** tab.

Note

This feature requires the PHP Memcache extension. See <http://php.net/manual/en/book.memcache.php> for details.

Option	Description	Default
Memcache	Enable connection to memcached servers to store temporary information.  <i>Requires the PHP memcache extension.</i>	Disabled
Memcache key prefix	When the memcache cluster is used by multiple applications, using unique prefixes for each of them helps avoid conflicts.	Tiki_
Memcache expiration	Duration for which the data will be kept.	3600 seconds
Memcache servers	Server list which may be accessed. For each server, the address, port and weight must be specified.  <i>One per line, with format of address port (weight); for example, "localhost:11211 (1)"</i>	None
Cache wiki data in memcache		Enabled
Cache wiki output in memcache		Enabled
Cache forum output in memcache		Enabled

The jQuery Sortable Tables feature must be activated for the sort feature to work.

Option	Description	Default
Memcache	Enable connection to memcached servers to store temporary information.  <i>Requires the PHP memcache extension.</i>	Disabled
Memcache key prefix	When the memcache cluster is used by multiple applications, using unique prefixes for each of them helps avoid conflicts.	Tiki_

Option	Description	Default
Memcache expiration	Duration for which the data will be kept.	3600 seconds
Memcache servers	Server list which may be accessed. For each server, the address, port and weight must be specified. ↳ One per line, with format of address port (weight) ; for example, "localhost:11211 (1)"	None
Cache wiki data in memcache		Enabled
Cache wiki output in memcache		Enabled
Cache forum output in memcache		Enabled

The jQuery Sortable Tables feature must be activated for the sort feature to work.

Option	Description	Default
Memcache	Enable connection to memcached servers to store temporary information. ↳ Requires the PHP memcache extension.	Disabled
Memcache key prefix	When the memcache cluster is used by multiple applications, using unique prefixes for each of them helps avoid conflicts.	Tiki_
Memcache expiration	Duration for which the data will be kept.	3600 seconds
Memcache servers	Server list which may be accessed. For each server, the address, port and weight must be specified. ↳ One per line, with format of address port (weight) ; for example, "localhost:11211 (1)"	None
Cache wiki data in memcache		Enabled
Cache wiki output in memcache		Enabled
Cache forum output in memcache		Enabled

The jQuery Sortable Tables feature must be activated for the sort feature to work.

Option	Description	Default
Memcache	Enable connection to memcached servers to store temporary information. ↳ Requires the PHP memcache extension.	Disabled

Option	Description	Default
Memcache key prefix	When the memcache cluster is used by multiple applications, using unique prefixes for each of them helps avoid conflicts.	Tiki_
Memcache expiration	Duration for which the data will be kept.	3600 seconds
Memcache servers	Server list which may be accessed. For each server, the address, port and weight must be specified. <i>↳ One per line, with format of address:port (weight); for example, "localhost:11211 (1)"</i>	None
Cache wiki data in memcache		Enabled
Cache wiki output in memcache		Enabled
Cache forum output in memcache		Enabled

The jQuery Sortable Tables feature must be activated for the sort feature to work.